

Work Smarter with Cost-Effective, Feature-Packed Thin Clients



The YESstation EXT is the newest member of the Affirmative family of thin clients featuring wired, wireless, fixed and portable devices for midrange budgets. All EXT models support PC peripherals such as printers, modems, monitors, keyboards, wireless adaptors and pointing devices. Windows CE models include a local Internet Explorer 6 browser, while Linux models include a Mozilla browser. Affirmative thin clients are ideal terminal replacements and less costly, more reliable alternatives to PCs. There are no moving parts, giving the EXT an impressive MTBF of well over 12 years.

The YESstation EXT thrives in harsh environments where dust and airborne contaminants are a problem for PCs, but they are equally at home in office environments where attractive styling and silent operation are important. The EXT's exceptionally small footprint, when vertically oriented, frees up valuable desk or bench space. The EXT's standard colors are black and silver, matching the current trend toward black monitors. Affirmative also offers matching input devices including mice and specialty keyboards with dual color-coded key caps that enhance user productivity when switching between 5250/3270 legacy applications and Windows/browser applications.



A complete array of ports and slots makes the 232X platform versatile

Why thin clients?

Thin clients (TC) are an alternative to PCs and workstations widely deployed in business operations. They are somewhat less expensive to buy, but enormously less expensive to maintain. There are no disk drives to crash, no viruses, no productivity-robbing games or movies and no way for a user to transfer files without authorization.

A TC is a display terminal that can also support a local printer and other PC peripherals, such as modems and wireless LAN adapters. Display terminals allow the user to work with Windows, Web browsers, UNIX and IBM mainframe applications without moving any files to the desktop. This eliminates the need for users to backup their hard drives, eliminates unauthorized applications and improves user productivity.

With the extended Affirmative family, thin is in



All Affirmative thin clients feature a built-in VNC server, allowing administrators to 'shadow' the terminal and take control, as if they were sitting at the user's workstation, from anywhere with network access.

YESstation EXT Hardware Specifications

Items

Processor

Input / Output connector support

Display Resolution & colors

Memory Support

Environment

Temperature

Relative Humidity

Power

Regulatory Compliance

Physical Characteristics

Dimensions (WxDxH)

Weight

Specifications

AMD 466 integrated processor, video and I/O

Two USB ports (1.1)
One serial port, COM1
Parallel printer port
Two PS/2 ports for keyboard and mouse
PCI slot
PCMCIA card slot supports wireless LAN adapter
Audio in/out ports
10/100 Ethernet port, auto sensing

VGA video, up to 1,600 x 1,200-dpi resolution

SDRAM -- 128 MB (max. 512 MB)
Compact Flash memory: 32 MB standard (max. 512 MB)

Operating: 5° C to 35° C (41° F to 95° F)
Storage: -10° C to 60° C (14° F to 140° F)
90% maximum, non-condensing
Internal power supply, 90-240 Volts AC, 50-60 Hz

FCC, CE, UL-approved, Lead-free

9.25 x 6.5 x 1.5 (inches)
3 Pounds

Windows CE Model 2325

- 128 MB DDR RAM, 32 MB Compact Flash
- Windows CE.NET with desktop, WBT, and kiosk viewing modes
- ICA 7.0, RDP 5.0 clients for access to Citrix and Windows server-based applications
- SNMP and Central Manager client modules
- Drivers for Cisco and other wireless cards
- Local Internet Explorer 6 Web browser
- Microsoft e-mail client
- Microsoft Office viewers
- Microsoft PDF Viewer
- TCP/IP with DNS and DHCP
- Point-to-Point Over Ethernet (PPPoE)
- Point-to-Point Tunneling Protocol (PPTP)
- Layer-2 Tunneling Protocol (L2TP)
- Wake on LAN (WOL)
- PXE

Windows CE Model 2322

- All features of Model 2325 plus -
- PowerTerm emulation IBM TN3270, TN5250, Digital VT52/100/200/320/420/520/525, ANSI-ANSI-BBS, SCO-ANSI, AT386, Wyse 50/60, DG D-412, Televideo TVI 925/950, HP 700/92, 700/96
- Affirmative exclusive viewing modes for IBM 5250 and 3270 users; choose text, Windows or GUI at no extra cost

Linux Model 2326

- 128 MB DDR RAM, 128 MB Compact Flash
- Linux 2.4.20
- ICA 7.0, RDP 5.0, and Tarantella for access to Citrix and Windows server-based applications
- XDM, VNC client and server
- Point-to-Point (PPP) via RS232C
- Point-to-Point Over Ethernet (PPPoE)
- Point-to-Point Tunneling Protocol (PPTP)
- SSH client
- Wake on LAN (WOL)
- PXE
- Master browser and load balancing for Citrix
- PowerTerm emulation IBM TN3270, TN5250, Digital VT52/100/200/320/420/520/525, ANSI-ANSI-BBS, SCO-ANSI, AT386, Wyse 50/60, DG D-412, Televideo TVI 925/950, HP 700/92, 700/96
- Affirmative exclusive viewing modes for IBM 5250 and 3270 users; choose text, Windows or GUI at no extra cost

Windows XP embedded Model 2327

- 256 MB DDR RAM
- 256 MB Compact Flash, 18 MB free
- Windows XPe
- Outlook Express
- Internet Explorer 6 Web browser
- ICA and RDP
- Other Windows applications subject to available storage

Authorized Distributor

